

**Description**

Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS1720H4L6A     |
| Minimum Qty (MOQ): | 15 EA            |
| NSN:               | 5320-01-507-4825 |
| Schedule B:        | 7616.10.3000     |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

# P/N NAS1720H4L6A Specifications

|                      |   |
|----------------------|---|
| Fastener Length:     | 0.513 Inches Maximum                          |
| Head Style:          | Universal                                     |
| Head Height:         | 0.075 Inches Minimum And 0.080 Inches Maximum |
| Shank Diameter:      | 0.190 Inches Nominal                          |
| Shank Style:         | Self-plugging Mechanically Locked Stem        |
| Head Major Diameter: | 0.370 Inches Minimum And 0.380 Inches Maximum |
| Expansion Device:    | Serrated Stem-type W                          |
| Grip Length:         | 0.297 Inches Minimum And 0.391 Inches Maximum |
| Material:            | Aluminum Alloy Sleeve                         |

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1720H4L6A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.