

**Description**

Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1720H5L8A
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-572-3494
Schedule B:	7616.10.3000
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS1720H5L8A Specifications

<b>Fastener Length:</b>	0.668 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.072 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.160 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.307 Inches Minimum And 0.317 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	Aircraft Applications
<b>Grip Length:</b>	0.422 Inches Minimum And 0.518 Inches Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Blind Rivet
<b>Special Features:</b>	Rivet,blind,protruding Head,mechanically Locked Spindle;total Length 10in;blind Side Max Grip Length 0.669;max Grip Clearance Range 1.19in
<b>Material:</b>	Aluminum Alloy 7075 Mandrel
<b>Material Document And Classification:</b>	Qq-a-430 T6 Fed Spec Single Material Response Mandrel
<b>Surface Treatment:</b>	Anodize Mandrel
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Yellow Mil Spec 1st Treatment Response Mandrel Or Mil-c-5541 Chem Film Mil Spec 2nd Treatment Response Mandrel

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1720H5L8A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.