

P/N NAS1720H6L5A

Military-Fasteners.com

Description

Mbc Rivet part number

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS1720H6L5A
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-572-3517
Schedule B:	7616.10.3000
ECCN:	EAR99



P/N NAS1720H6L5A Specifications

Fastener Length:	0.516 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.085 Inches Maximum
Shank Diameter:	0.189 Inches Minimum And 0.194 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.370 Inches Minimum And 0.380 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Aircraft Applications
Grip Length:	0.234 Inches Minimum And 0.328 Inches Maximum
Part Name Assigned By Controlling Agency:	Blind Rivet
Special Features:	Rivet,blind,protruding Head,mechanically Locked Spindle;total Length 8in;blind Side Max Grip Length 0.516;max Grip Clearance Range 0.90in
Material:	Aluminum Alloy 7075 Mandrel
Material Document And Classification:	Qq-a-430 T6 Fed Spec Single Material Response Mandrel
Surface Treatment:	Anodize Mandrel
Surface Treatment Document And Classification:	Mil-a-8625 Yellow Mil Spec 1st Treatment Response Mandrel Or Mil-c-5541 Chem Film Mil Spec 2nd Treatment Response Mandrel

How to Order

Order this mbc rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/NAS1720H6L5A</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.