

Description

Mbc Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1720H6L5A |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-01-572-3517 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1720H6L5A Specifications

| | |
|---|---|
| Fastener Length: | 0.516 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.085 Inches Maximum |
| Shank Diameter: | 0.189 Inches Minimum And 0.194 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.370 Inches Minimum And 0.380 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| End Item Identification: | Aircraft Applications |
| Grip Length: | 0.234 Inches Minimum And 0.328 Inches Maximum |
| Part Name Assigned By Controlling Agency: | Blind Rivet |
| Special Features: | Rivet,blind,protruding Head,mechanically Locked Spindle;total Length 8in;blind Side Max Grip Length 0.516;max Grip Clearance Range 0.90in |
| Material: | Aluminum Alloy 7075 Mandrel |
| Material Document And Classification: | Qq-a-430 T6 Fed Spec Single Material Response Mandrel |
| Surface Treatment: | Anodize Mandrel |
| Surface Treatment Document And Classification: | Mil-a-8625 Yellow Mil Spec 1st Treatment Response Mandrel Or Mil-c-5541 Chem Film Mil Spec 2nd Treatment Response Mandrel |

How to Order

Order this mbc rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1720H6L5A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.