

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1720KE4L2F
Minimum Qty (MOQ):	30 EA
NSN:	5320-01-475-2411
Schedule B:	7616.10.3000
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1720KE4L2F Specifications

Fastener Length:	0.263 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.059 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.129 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.245 Inches Minimum And 0.255 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.047 Inches Minimum And 0.141 Inches Maximum
Material:	Aluminum Alloy 7075 Stem
Material:	Aluminum Alloy 7075 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Stem
Surface Treatment Document And Classification:	Mil-a-6625 Mil Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1720KE4L2F> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.