

**Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1720KE4L2F
Minimum Qty (MOQ):	30 EA
NSN:	5320-01-475-2411
Schedule B:	7616.10.3000
ECCN:	9A991



NO IMAGE  
AVAILABLE

## P/N NAS1720KE4L2F Specifications

<b>Fastener Length:</b>	0.263 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.059 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.129 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.245 Inches Minimum And 0.255 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.047 Inches Minimum And 0.141 Inches Maximum
<b>Material:</b>	Aluminum Alloy 7075 Stem
<b>Material:</b>	Aluminum Alloy 7075 Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Stem
<b>Surface Treatment Document And Classification:</b>	Mil-a-6625 Mil Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1720KE4L2F> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.