

Description

Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1721C5L3W
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-573-4687
Schedule B:	7318.23.0000
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N NAS1721C5L3W Specifications

Fastener Length:	0.338 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.225 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.109 Inches Minimum And 0.203 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy Sleeve
Surface Treatment:	Cadmium Sleeve

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1721C5L3W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.