

# **P/N NAS1721C5L3W**

### **Description**

Rivet part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:

Minimum Qty (MOQ):

5 EA

NSN: 5320-01-573-4687

Schedule B: 7318.23.0000

ECCN: EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1721C5L3W Specifications

Fastener Length:	0.338 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.225 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.109 Inches Minimum And 0.203 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy Sleeve
Surface Treatment:	Cadmium Sleeve

# **How to Order**

Order this rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1721C5L3W">https://military-fasteners.com/rivets/blind+rivets/NAS1721C5L3W</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.