

**Description**

Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1721C5L3W
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-573-4687
Schedule B:	7318.23.0000
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1721C5L3W Specifications

<b>Fastener Length:</b>	0.338 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.225 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.109 Inches Minimum And 0.203 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy Sleeve
<b>Surface Treatment:</b>	Cadmium Sleeve

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1721C5L3W> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.