

Description

Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1721H5L6A
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-572-3919
Schedule B:	7616.10.3000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1721H5L6A Specifications

Fastener Length:	0.644 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.285 Inches Minimum And 0.286 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Aircraft Applications
Grip Length:	0.297 Inches Minimum And 0.391 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Blind Rivet Flush Head
Special Features:	Rivet-blind,100deg Flush Head (ms20426 Head), Mechanically Locked Spindle;max Length 0.89in
Material:	Aluminum Alloy 7075 Mandrel
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Mandrel
Surface Treatment:	Anodize Mandrel
Surface Treatment Document And Classification:	Mil-a-8625 Yellow Mil Spec 1st Treatment Response Mandrel Or Mil-c-5541 Chem Film Mil Spec 2nd Treatment Response Mandrel

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1721H5L6A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.