

Description

Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1721H5L7A
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-577-0232
Schedule B:	7616.10.3000
ECCN:	9A991



NO IMAGE
AVAILABLE

P/N NAS1721H5L7A Specifications

Part Name Assigned By Controlling Agency:	Rivet,blind
Special Features:	Rivet: Length Max: 0.586 Inch;grip Range,min: 0.359 Inch,max 0.453 Inch;material,sleeve: 2014-t4 Alum Alloy Per Qq-a-430 (code H);spindle: 7075-t6 Alum Alloy Per Qq-a-430;finish,sleeve: Clear Anodize Per Mil-a-8625,lubricate As Necessary To Insure Proper Function (code A),spindle: Yellow Anodize Per Mil-a-8625 Or Chemical Film Per Mil-c-5541,lubricate As Necessary To Insure Proper Function;rivet Size Normal Diameter: 0.156 Inch,shank Diameter: 0.156 Inch
Material:	Aluminum Alloy Sleeve

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1721H5L7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.