

P/N NAS1721H5L7A

Description

Rivet part number

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

 SKU / Model:
 NAS1721H5L7A

 Minimum Qty (MOQ):
 10 EA

 NSN:
 5320-01-577-0232

 Schedule B:
 7616.10.3000

 ECCN:
 9A991



^{*} See page 2 for technical characteristics

P/N NAS1721H5L7A Specifications

Part Name Assigned By Controlling Agency:	Rivet,blind
Special Features:	Rivet: Length Max: 0.586 Inch;grip Range,min: 0.359 Inch,max 0.453 Inch;material,sleeve: 2014-t4 Alum Alloy Per Qq-a-430 (code H);spindle: 7075-t6 Alum Alloy Per Qq-a-430;finish,sleeve: Clear Anodize Per Mil-a-8625,lubricate As Necessary To Insure Proper Function (code A),spindle: Yellow Anodize Per Mil-a-8625 Or Chemical Film Per Mil-c-5541,lubricate As Necessary To Insure Proper Function;rivet Size Normal Diameter: 0.156 Inch,shank Diameter: 0.156 Inch
Material:	Aluminum Alloy Sleeve

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1721H5L7A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1721H5L7A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1721H5L7A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1721H5L7A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/NAS1721H5L7A and selecting the quantity you want then click "add to cart".