

Description

thread: 10-32, self-locking nut with captive washer, NAS1726 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS17263E
Minimum Qty (MOQ):	10
NSN:	5310-01-308-4822
Schedule B:	7318.16.0000
ECCN:	EAR99



P/N NAS1726-3E Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.380 Inches Maximum
Counterbore Diameter:	0.211 Inches Minimum Nut And 0.221 Inches Maximum Nut
Lubrication:	Dry Film Lubricant
Overall Height:	0.223 Inches Minimum And 0.243 Inches Maximum
Nut Style:	Flat With Turned Up Edge
Width Across Flats:	0.213 Inches Minimum And 0.221 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Specification/standard Data:	80205-nas1726 Professional/industrial Association Standard

How to Order

Order this self-locking assembled washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+assembled+washer+nuts/NAS1726-3E and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.