

Description

Thread Size: 1/4", Head Width: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS17264D |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5310-01-057-9360 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1726-4D Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.460 Inches Maximum |
| Counterbore Diameter: | 0.277 Inches Minimum Nut And 0.287 Inches Maximum Nut |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.271 Inches Minimum And 0.291 Inches Maximum |
| Nut Style: | Flat With Turned Up Edge |
| Nut Counterbore Depth: | 0.072 Inches Minimum Nut And 0.087 Inches Maximum Nut |
| Width Across Flats: | 0.274 Inches Minimum And 0.284 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 28 |
| Hardness Rating: | Nut Rockwell C Scale 36 Min And Rockwell C Scale 40 Max,washer Rockwell C Scale 40 Min And Rockwell C Scale 45 Max |
| Nominal Thread Size: | 0.250 Inches |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Steel Comp 1050 Washer |
| Material: | Steel Comp 4340 Nut Or Steel Comp 8740 Nut |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1726 Professional/industrial Association Standard |

How to Order

Order this self-locking assembled washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+assembled+washer+nuts/NAS1726-4D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.