

Description

Thread Size: 1/4", Head Width: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS17264D
Minimum Qty (MOQ):	20
NSN:	5310-01-057-9360
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1726-4D Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.460 Inches Maximum
Counterbore Diameter:	0.277 Inches Minimum Nut And 0.287 Inches Maximum Nut
Lubrication:	Dry Film Lubricant
Overall Height:	0.271 Inches Minimum And 0.291 Inches Maximum
Nut Style:	Flat With Turned Up Edge
Nut Counterbore Depth:	0.072 Inches Minimum Nut And 0.087 Inches Maximum Nut
Width Across Flats:	0.274 Inches Minimum And 0.284 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Hardness Rating:	Nut Rockwell C Scale 36 Min And Rockwell C Scale 40 Max,washer Rockwell C Scale 40 Min And Rockwell C Scale 45 Max
Nominal Thread Size:	0.250 Inches
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Comp 1050 Washer
Material:	Steel Comp 4340 Nut Or Steel Comp 8740 Nut
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1726 Professional/industrial Association Standard

How to Order

Order this self-locking assembled washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+assembled+washer+nuts/NAS1726-4D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.