

**Description**

thread: 1/4-28, steel alloy, locknut with captive washer, NAS1726 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS17264E
Minimum Qty (MOQ):	25
NSN:	5310-01-139-3286
Schedule B:	7318.16.0085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS1726-4E Specifications

<b>Thread Class:</b>	2b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Washer Outside Diameter:</b>	0.460 Inches Maximum
<b>Lubrication:</b>	Soluble Lubricant
<b>Overall Height:</b>	0.271 Inches Minimum And 0.291 Inches Maximum
<b>Nut Style:</b>	Flat With Turned Up Edge
<b>Nut Counterbore Depth:</b>	0.072 Inches Minimum Overall And 0.087 Inches Maximum Overall
<b>Width Across Flats:</b>	0.274 Inches Minimum And 0.284 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Maximum
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	28
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Material:</b>	Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Specification/standard Data:</b>	80205-nas1726 Professional/industrial Association Standard

## How to Order

Order this self-locking assembled washer nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+assembled+washer+nuts/NAS1726-4E](https://military-fasteners.com/nuts/self_locking+assembled+washer+nuts/NAS1726-4E) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.