



★ FASTENERS

Military-Fasteners.com

P/N NAS1726-4E

Description

thread: 1/4-28, steel alloy, locknut with captive washer, NAS1726 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS17264E
Minimum Qty (MOQ):	25
NSN:	5310-01-139-3286
Schedule B:	7318.16.0085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1726-4E Specifications

Thread Class:	2b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.460 Inches Maximum
Lubrication:	Soluble Lubricant
Overall Height:	0.271 Inches Minimum And 0.291 Inches Maximum
Nut Style:	Flat With Turned Up Edge
Nut Counterbore Depth:	0.072 Inches Minimum Overall And 0.087 Inches Maximum Overall
Width Across Flats:	0.274 Inches Minimum And 0.284 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Hardness Rating:	36.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Specification/standard Data:	80205-nas1726 Professional/industrial Association Standard

How to Order

Order this self-locking assembled washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+assembled+washer+nuts/NAS1726-4E and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.