



Military-Fasteners.com

P/N NAS1726-5D

Description

Thread Size: 1/4", Head Width: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS17265D
Minimum Qty (MOQ):	10
NSN:	5310-01-058-0765
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1726-5D Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.560 Inches Maximum
Counterbore Diameter:	0.342 Inches Minimum Nut And 0.352 Inches Maximum Nut
Lubrication:	Dry Film Lubricant
Overall Height:	0.316 Inches Minimum And 0.336 Inches Maximum
Nut Style:	Flat With Turned Up Edge
Nut Counterbore Depth:	0.072 Inches Minimum Nut And 0.087 Inches Maximum Nut
Width Across Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches
Special Features:	Washer Rockwell C Scale 40 Min Rockwell C Scale 45 Max
Material:	Steel Comp 1050 Washer
Material:	Steel Comp 4340 Nut Or Steel Comp 8740 Nut
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1726 Professional/industrial Association Standard

How to Order

Order this self-locking assembled washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+assembled+washer+nuts/NAS1726-5D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.