

Description

Thread Size: 3/8", Nut Height: 1/2", Head Width: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1727C6E
Minimum Qty (MOQ):	1 EA
NSN:	5310-01-059-6007
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1727C6E Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Soluble Lubricant
Nut Style:	Single Ball Seat, Double Hexagon
Ball Seat Radius:	0.375 Inches Minimum And 0.385 Inches Maximum
Nut Height:	0.445 Inches Minimum And 0.455 Inches Maximum
Width Across Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Special Features:	0.531 In. Min And 0.537 In. Max Washer Id,0.780 In. Min And 0.790 In. Max Washer Od,0.170 In. Min And 0.180 In. Max Washer Thickness,0.099 In Nom Shoulder Height 0.435 In. Min And 0.455 In. Max Spherical Radius
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this 2 piece assembly nut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1727C6E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.