

**Description**

NAS1738 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1738M42
Minimum Qty (MOQ):	10
NSN:	5320-00-938-2073
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N NAS1738M4-2 Specifications

<b>Fastener Length:</b>	0.265 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.139 Inches Minimum And 0.143 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Shear Strength:</b>	710 Single Pounds Per Square Inch
<b>Material:</b>	Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Locking Ring
<b>Specification/standard Data:</b>	80205-nas1738 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1738M4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.