

Description

NAS1738 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online](#)**Additional Information****Alternate Part Numbers**CR2539-4-3 CR2539-4-03

SKU / Model:	NAS1738M43
Minimum Qty (MOQ):	10
NSN:	5320-00-839-2146
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1738M4-3 Specifications

Fastener Length:	0.328 Inches Nominal
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall
Surface Treatment:	Any Acceptable Overall
Specification/standard Data:	80205-nas1738 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1738M4-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.