

**Description**

NAS1739B5-6 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1739B56          |
| Minimum Qty (MOQ):      | 20                  |
| NSN:                    | 5320-00-143-6395    |
| Schedule B:             | 8308.20.6000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1739B5-6 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.562 Inches Maximum   |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                         |
| <b>Shank Diameter:</b>                                | 0.172 Inches Minimum And 0.176 Inches Maximum  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.282 Inches Minimum And 0.290 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.313 Inches Minimum And 0.375 Inches Maximum  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Locking Ring   |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec All Material Responses Locking Ring  |
| <b>Surface Treatment:</b>                             | Anodize Sleeve Or Chromate Sleeve  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| <b>Specification/standard Data:</b>                   | 80205-nas1739 Professional/Industrial Association Standard   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1739B5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.