

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1739C45
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-111-7651
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1739C4-5 Specifications

Fastener Length:	0.469 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Head Major Diameter:	0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 600 Sleeve
Material Document And Classification:	Ams 5687 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Stem
Specification/standard Data:	80205-nas1739 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1739C4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.