

**Description**

NAS1739 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2538-4-03](#) [CR2538-4-3](#)

SKU / Model:	NAS1739M43
Minimum Qty (MOQ):	10
NSN:	5320-00-181-6355
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1739M4-3 Specifications

<b>Fastener Length:</b>	0.344 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.139 Inches Minimum And 0.143 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Shear Strength:</b>	785 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Locking Ring
<b>Specification/standard Data:</b>	80205-nas1739 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1739M4-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.