

# P/N NAS1750-08DL5

# **Description**

threaded stem, drive nut, jo-bolt, NAS1750 series rivet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

### **Additional Information**

SKU / Model: NAS175008DL5

Minimum Qty (MOQ):

NSN: 5320-01-339-1954

Schedule B: 7318.15.2010

ECCN: 9A991

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1750-08DL5 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.1780 Inches Minimum And 0.1800 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Head Major Diameter:	0.296 Inches Minimum
<b>Expansion Device:</b>	Threaded Stem
Lubrication:	Dry Film Or Paraffin Wax Or Cetyl Alcohol
Grip Length:	0.282 Inches Minimum And 0.344 Inches Maximum
Features Provided:	Drive Nut
Hardness Rating:	39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Drive Nut Steel,color Coded Gold,with A Corrosion Retardent Coating
Material:	Aluminum Alloy 7075 Nut
Material:	Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve
Material:	Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt
Material Document And Classification:	Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt
Material Document And Classification:	Qq-a-225/9,t6 Fed Spec Single Material Response Nut
Surface Treatment:	Anodize Nut
Surface Treatment:	Cadmium Bolt And Chromate Bolt
Surface Treatment:	Passivate Sleeve And Cadmium Sleeve Or Passivate Sleeve And Cadmium Sleeve And Chromate Sleeve
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty 1,cl 3 Fed Spec 1st Treatment Response Sleeve Or Qq-p-35 Fed Spec 2nd Treatment Response Sleeve And Qq-p-416,ty 2,cl 3 Fed Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt
Specification/standard Data:	80205-nas1674 Professional/industrial Association Standard

# Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1750-08DL5">https://military-fasteners.com/rivets/blind+rivets/NAS1750-08DL5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1750-08DL5">https://military-fasteners.com/rivets/blind+rivets/NAS1750-08DL5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1750-08DL5">https://military-fasteners.com/rivets/blind+rivets/NAS1750-08DL5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1750-08DL5">https://military-fasteners.com/rivets/blind+rivets/NAS1750-08DL5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1750-08DL5">https://military-fasteners.com/rivets/NAS1750-08DL5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1750-08DL5">https://military-fasteners.com/rivets/NAS1750-08DL5</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1750-08DL5">https://military-fasteners.com/rivets/NAS1750-08DL5</a> and selecting the quantity you want <a href="https://military-fasteners.com/rivets/NAS1750-08DL5">https://military-fasteners.com/rivets/NAS1750-08DL5</a> and selecting the property of t