

Description

grip range: 0.220" - 0.281", diameter: 0.164", general purpose blind rivet, flush head, internally threaded, external sleeve, oversized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS175008L4
Minimum Qty (MOQ):	5
NSN:	5320-01-012-4577
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS1750-08L4 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.178 Inches Minimum And 0.180 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Head Major Diameter:	0.296 Inches Minimum And 0.332 Inches Maximum
Expansion Device:	Threaded Stem
Grip Length:	0.220 Inches Minimum And 0.281 Inches Maximum
Hardness Rating:	39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt
Hardness Rating:	39.0 Rockwell C Minimum Nut And 43.0 Rockwell C Maximum Nut
Shear Strength:	3355 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt
Material:	Steel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp 4130 Nut
Material:	Steel Comp 304 Sleeve Or Steel Comp 303f Sleeve Or Steel Comp 303 Sleeve
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-6758 Mil Spec 3rd Material Response Nut
Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Ams 5641 Assn Std 2nd Material Response Sleeve Or Astm A582 Assn Std 3rd Material Response Sleeve
Surface Treatment:	Cadmium Bolt And Chromate Bolt
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Cadmium Sleeve And Passivate Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 1,c1 3 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Bolt
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Nut
Specification/standard Data:	80205-nas1750 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1750-08L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.