

# P/N NAS1750-08L5

## **Description**

Jo-Bolt, NAS1750 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

### **Additional Information**

SKU / Model: NAS175008L5

Minimum Qty (MOQ): 5

NSN: 5320-00-814-9990

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









# P/N NAS1750-08L5 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.178 Inches Minimum And 0.180 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Head Major Diameter:	0.325 Inches Minimum And 0.332 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
Lubrication:	Dry Film Or Wax
Grip Length:	0.281 Inches Minimum And 0.344 Inches Maximum
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt
Hardness Rating:	39.0 Rockwell C Minimum Nut And 43.0 Rockwell C Maximum Nut
Shear Strength:	3355 Double Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	Annealed Overall
Material:	Steel Comp 303f Sleeve
Material:	Steel Comp 4130 Stem Or Steel Comp 8740 Stem Or Steel Comp 4140 Stem
Material:	Steel Comp 4130 Body Or Steel Comp 8740 Body Or Steel Comp 4140 Body
Material Document And Classification:	Ams 5641 Assn Std Single Material Response Sleeve
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Body Or Mil-s-6049 Mil Spec 2nd Material Response Body Or Mil-s-5626 Mil Spec 3rd Material Response Body
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Stem Or Mil-s-6049 Mil Spec 2nd Material Response Stem Or Mil-s-5626 Mil Spec 3rd Material Response Stem
Surface Treatment:	Cadmium Bolt And Chromate Bolt
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Cadmium Sleeve And Passivate Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Nut

# **How to Order** Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1750-08L5">https://military-fasteners.com/rivets/blind+rivets/NAS1750-08L5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order. Provided by Military-Fasteners.com