

**Description**

Jo-bolt part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS17503DL13
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-339-1994
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

# P/N NAS1750-3DL13 Specifications

<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.2130 Inches Minimum And 0.2150 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Head Major Diameter:</b>	0.342 Inches Minimum
<b>Expansion Device:</b>	Threaded Stem
<b>Lubrication:</b>	Dry Film Or Paraffin Wax Or Cetyl Alcohol
<b>Grip Length:</b>	0.782 Inches Minimum And 0.844 Inches Maximum
<b>Features Provided:</b>	Drive Nut
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Special Features:</b>	Drive Nut Steel,color Coded Gold,with A Corrosion Retardent Coating
<b>Material:</b>	Aluminum Alloy 7075 Nut
<b>Material:</b>	Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve
<b>Material:</b>	Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt
<b>Material Document And Classification:</b>	Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt
<b>Material Document And Classification:</b>	Qq-a-225/9,t6 Fed Spec Single Material Response Nut
<b>Surface Treatment:</b>	Anodize Nut
<b>Surface Treatment:</b>	Cadmium Bolt And Chromate Bolt
<b>Surface Treatment:</b>	Passivate Sleeve And Cadmium Sleeve Or Passivate Sleeve And Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Nut
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty 1,cl 3 Fed Spec 1st Treatment Response Sleeve Or Qq-p-35 Fed Spec 2nd Treatment Response Sleeve And Qq-p-416,ty 2,cl 3 Fed Spec 2nd Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt
<b>Specification/standard Data:</b>	80205-nas1674 Professional/industrial Association Standard

## How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1750-3DL13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.