

Description

Jo-bolt part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS17503DL14 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-354-0003 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1750-3DL14 Specifications

| | |
|---|--|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.2130 Inches Minimum And 0.2150 Inches Maximum |
| Shank Style: | Threaded Self-plugging Shank W/sleeve |
| Head Major Diameter: | 0.342 Inches Minimum |
| Expansion Device: | Threaded Stem |
| Lubrication: | Dry Film Or Paraffin Wax Or Cetyl Alcohol |
| Grip Length: | 0.845 Inches Minimum And 0.906 Inches Maximum |
| Features Provided: | Drive Nut |
| Hardness Rating: | 39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Special Features: | Drive Nut Steel,color Coded Gold,with A Corrosion Retardent Coating |
| Material: | Aluminum Alloy 7075 Nut |
| Material: | Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve |
| Material: | Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt |
| Material Document And Classification: | Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt |
| Material Document And Classification: | Qq-a-225/9,t6 Fed Spec Single Material Response Nut |
| Surface Treatment: | Anodize Nut |
| Surface Treatment: | Cadmium Bolt And Chromate Bolt |
| Surface Treatment: | Passivate Sleeve And Cadmium Sleeve Or Passivate Sleeve And Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Nut |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty 1,cl 3 Fed Spec 1st Treatment Response Sleeve Or Qq-p-35 Fed Spec 2nd Treatment Response Sleeve And Qq-p-416,ty 2,cl 3 Fed Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt |
| Specification/standard Data: | 80205-nas1674 Professional/industrial Association Standard |

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1750-3DL14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.