

Description

Jo-bolt part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS17503DL7
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-306-9799
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1750-3DL7 Specifications

Shank Diameter:	0.2130 Inches Minimum And 0.2150 Inches Maximum
Head Major Diameter:	0.342 Inches Minimum
Features Provided:	Drive Nut
Hardness Rating:	39.0 Rockwell C Minimum Nut And 43.0 Rockwell C Maximum Nut
Material:	Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve
Material:	Steel Comp 4130 Nut Or Steel Comp 4140 Nut Or Steel Comp 8740 Nut
Material Document And Classification:	Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Nut Or Mil-s-5626 Mil Spec 2nd Material Response Nut Or Mil-s-6049 Mil Spec 3rd Material Response Nut
Surface Treatment:	Cadmium Bolt And Chromate Bolt
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Passivate Sleeve And Cadmium Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty 1,cl 3 Fed Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Nut
Specification/standard Data:	80205-nas1750 Professional/Industrial Association Standard

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1750-3DL7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.