

**Description**

grip range: 0.157" - 0.219", diameter: 0.20", general purpose, flush head, internally threaded, external sleeve, oversized, NAS1750 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS17503L3
Minimum Qty (MOQ):	5
NSN:	5320-00-323-4202
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

# P/N NAS1750-3L3 Specifications

<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.213 Inches Minimum And 0.215 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Head Major Diameter:</b>	0.342 Inches Minimum And 0.385 Inches Maximum
<b>Expansion Device:</b>	Threaded Stem
<b>Grip Length:</b>	0.157 Inches Minimum And 0.219 Inches Maximum
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Nut And 43.0 Rockwell C Maximum Nut
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Special Features:</b>	Self-locking
<b>Material:</b>	Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303f Sleeve
<b>Material:</b>	Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt
<b>Material:</b>	Steel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp 4130 Nut
<b>Material Document And Classification:</b>	Astm A582 Assn Std 1st Material Response Sleeve Or Qq-s-763 Fed Spec 2nd Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-6758 Mil Spec 3rd Material Response Nut
<b>Surface Treatment:</b>	Cadmium Bolt And Chromate Bolt
<b>Surface Treatment:</b>	Cadmium Nut And Chromate Nut
<b>Surface Treatment:</b>	Passivate Sleeve And Cadmium Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416 Ty 1 Cl 3 Fed Spec 2nd Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Bolt
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Nut
<b>Specification/standard Data:</b>	80205-nas1750 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1750-3L3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.