

**Description**

Fastener Length: 25/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS17504L4
Minimum Qty (MOQ):	1
NSN:	5320-00-063-7952
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

# P/N NAS1750-4L4 Specifications

<b>Fastener Length:</b>	0.366 Inches Minimum And 0.396 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.274 Inches Minimum And 0.276 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Head Major Diameter:</b>	0.499 Inches Minimum And 0.507 Inches Maximum
<b>Expansion Device:</b>	Threaded Stem
<b>Lubrication:</b>	Dry Film Or Wax
<b>Grip Length:</b>	0.219 Inches Minimum And 0.281 Inches Maximum
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Shear Strength:</b>	9000 Double Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Special Features:</b>	Self-locking
<b>Material:</b>	Steel Comp 303f Sleeve
<b>Material:</b>	Steel Comp 4130 Stem Or Steel Comp 8740 Stem Or Steel Comp 4140 Stem
<b>Material:</b>	Steel Comp 4130 Body Or Steel Comp 8740 Body Or Steel Comp 4140 Body
<b>Material Document And Classification:</b>	Ams 5641 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Body Or Mil-s-6049 Mil Spec 2nd Material Response Body Or Mil-s-5626 Mil Spec 3rd Material Response Body
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Stem Or Mil-s-6049 Mil Spec 2nd Material Response Stem Or Mil-s-5626 Mil Spec 3rd Material Response Stem
<b>Surface Treatment:</b>	Cadmium Body
<b>Surface Treatment:</b>	Cadmium Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Body
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem
<b>Specification/standard Data:</b>	80205-nas1750 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1750-4L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.