

## Description

Fastener Length: 25/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS17504L4                                  |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5320-00-063-7952                            |
| Schedule B:             | 7318.15.8085                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

# P/N NAS1750-4L4 Specifications

|  |  |
|--|--|
| Fastener Length:                               | 0.366 Inches Minimum And 0.396 Inches Maximum  |
| Head Style:                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)   |
| Shank Diameter:                                | 0.274 Inches Minimum And 0.276 Inches Maximum  |
| Shank Style:                                   | Threaded Self-plugging Shank W/sleeve  |
| Head Major Diameter:                           | 0.499 Inches Minimum And 0.507 Inches Maximum  |
| Expansion Device:                              | Threaded Stem  |
| Lubrication:                                   | Dry Film Or Wax  |
| Grip Length:                                   | 0.219 Inches Minimum And 0.281 Inches Maximum  |
| Minimum Tensile Strength:                      | 180000 Pounds Per Square Inch  |
| Shear Strength:                                | 9000 Double Pounds Per Square Inch   |
| Countersink Angle:                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| Special Features:                              | Self-locking   |
| Material:                                      | Steel Comp 303f Sleeve   |
| Material:                                      | Steel Comp 4130 Stem Or Steel Comp 8740 Stem Or Steel Comp 4140 Stem   |
| Material:                                      | Steel Comp 4130 Body Or Steel Comp 8740 Body Or Steel Comp 4140 Body   |
| Material Document And Classification:          | Ams 5641 Assn Std Single Material Response Sleeve  |
| Material Document And Classification:          | Mil-s-6758 Mil Spec 1st Material Response Body Or Mil-s-6049 Mil Spec 2nd Material Response Body Or Mil-s-5626 Mil Spec 3rd Material Response Body |
| Material Document And Classification:          | Mil-s-6758 Mil Spec 1st Material Response Stem Or Mil-s-6049 Mil Spec 2nd Material Response Stem Or Mil-s-5626 Mil Spec 3rd Material Response Stem |
| Surface Treatment:                             | Cadmium Body   |
| Surface Treatment:                             | Cadmium Sleeve   |
| Surface Treatment:                             | Cadmium Stem   |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Sleeve   |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Body   |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem   |
| Specification/standard Data:                   | 80205-nas1750 Professional/industrial Association Standard   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1750-4L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.