

P/N NAS1766-08

Description

Thread Size: 1/8", Nut Length: 5/8", Nut Height: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS176608

Minimum Qty (MOQ): 5 EA

NSN: 5310-01-047-0407

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1766-08 Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Counterbore Diameter: | 0.168 Inches Minimum Nut |
| Lubrication: | Dry Film Lubricant |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.680 Inches Maximum |
| Nut Height: | 0.205 Inches Maximum |
| Nut Counterbore Depth: | 0.062 Inches Minimum Nut |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.339 Inches Minimum And 0.349 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjc |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.164 Inches |
| Material: | Steel Overall |
| Material Document And Classification: | Mil-n-25027 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1766-08 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.