

**Description**

Thread Size: 3/16", Nut Length: 25/32", Nut Height: 13/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1766CL3
Minimum Qty (MOQ):	5
NSN:	5310-01-482-6726
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1766CL3 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.786 Inches Nominal
<b>Nut Height:</b>	0.205 Inches Nominal
<b>Nut Counterbore Depth:</b>	0.194 Inches Nominal Nut
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.339 Inches Minimum And 0.349 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Width:</b>	0.484 Inches Minimum And 0.488 Inches Maximum
<b>End Item Identification:</b>	V2 Aircraft
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	49.0 Rockwell C Nominal
<b>Nominal Thread Size:</b>	0.192 Inches
<b>Thread Tolerance Class:</b>	3 Internal
<b>Part Name Assigned By Controlling Agency:</b>	Nut,self-locking,plate-corner,counterbored,floating,125 Ksi FtU,450 Degrees
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams5525 National Std/spec Single Material Response Overall Or Ams5737 National Std/spec Single Material Response Overall
<b>Specification/standard Data:</b>	80205 - Nas1766 Professional/industrial Association Standard

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1766CL3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.