

## **P/N NAS1766CL4**

### **Description**

Thread Size: 1/4", Nut Length: 1-5/64", Nut Height: 19/64

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1766CL4

Minimum Qty (MOQ): 2

NSN: 5310-01-434-3280

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)













# **P/N NAS1766CL4 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.254 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.079 Inches Maximum
Nut Height:	0.312 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Width:	0.705 Inches Minimum And 0.709 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Overall
Specification/standard Data:	80205-nas1766 Professional/industrial Association Standard

## **How to Order**

Order this locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS1766CL4">https://military-fasteners.com/nuts/locknuts/NAS1766CL4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.