

Description

Fastener Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1768D66 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-00-004-3517 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N NAS1768D6-6 Specifications

| | |
|---|--|
| Fastener Length: | 0.517 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.200 Inches Minimum And 0.204 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Special Features: | Stem Dyed Blue |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2017 Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Surface Treatment: | Chromate Stem |
| Surface Treatment: | Anodize Sleeve Or Chromate Sleeve |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2,cl 1 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541,cl 1a Mil Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Mil-c-5541,cl 1a Mil Spec Single Treatment Response Stem |
| Specification/standard Data: | 80205-nas1768 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1768D6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.