



Military-Fasteners.com

P/N NAS1768MW5-2

Description

Fastener Length: "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1768MW52
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-007-3302
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



\* See page 2 for technical characteristics

## P/N NAS1768MW5-2 Specifications

<b>Fastener Length:</b>	0.244 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Material:</b>	Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Sleeve
<b>Specification/standard Data:</b>	80205-nas1768 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1768MW5-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.