



Military-Fasteners.com

P/N NAS1768MW5-3

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1768MW53
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-007-3303
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N NAS1768MW5-3 Specifications

Fastener Length:	0.375 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.127 Inches Minimum And 0.187 Inches Maximum
Shear Strength:	1290 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Overall
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1768MW5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.