

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1769D42
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-004-3509
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N NAS1769D4-2 Specifications

Fastener Length:	0.281 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	480 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Stem Dyed Blue
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2017 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Stem
Surface Treatment:	Anodize Sleeve
Surface Treatment Document And Classification:	Mil-a-8625,ty 1,cl 1 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-c-5541,cl 1a Mil Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1769 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1769D4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.