

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1769D52
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-006-0796
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N NAS1769D5-2 Specifications

Fastener Length:	0.312 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.172 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Stem Dyed Blue
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Stem
Material:	Aluminum Alloy 2017 Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 1 Mil Spec 1st Treatment Response Overall Or Mil-c-5541,class 1a Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas1769 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1769D5-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.