

**Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1769D54
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-006-0792
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N NAS1769D5-4 Specifications

<b>Fastener Length:</b>	0.437 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.172 Inches Minimum And 0.176 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Shear Strength:</b>	935 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Stem Dyed Blue
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 7075 Stem
<b>Material:</b>	Aluminum Alloy 2017 Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2,class 1 Mil Spec 1st Treatment Response Overall Or Mil-c-5541,class 1a Mil Spec 2nd Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1769 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1769D5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.