

P/N NAS1779C3M

Description

Thread Size: 1/4", Nut Length: 3/4", Nut Height: 1/4

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

10AX86A307M12

SKU / Model: NAS1779C3M

Minimum Qty (MOQ): 10

NSN: 5310-01-285-2786

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N NAS1779C3M Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Base
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.739 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Plate Width:	0.290 Inches Minimum And 0.416 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Base
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Mounting Hole Center To Base:	0.100 Inches Minimum
Center To Center Distance Between Mounting Holes Along Length:	0.498 Inches Minimum And 0.502 Inches Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Special Features:	May Have Eyelets 0.140 In. Max H
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1779 Professional/industrial Association Standard

How to Order

