

**Description**

Thread Size: 1/4", Nut Length: 3/4", Nut Height: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1779R3
Minimum Qty (MOQ):	10 EA
NSN:	5310-01-242-8720
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1779R3 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.194 Inches Minimum Base
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.739 Inches Maximum
<b>Nut Height:</b>	0.250 Inches Maximum
<b>Plate Thickness:</b>	0.047 Inches Maximum
<b>Plate Width:</b>	0.290 Inches Minimum And 0.416 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.062 Inches Minimum Base
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Mounting Hole Center To Base:</b>	0.100 Inches Minimum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.498 Inches Minimum And 0.502 Inches Maximum
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.1900 Inches
<b>Material:</b>	Steel Comp 1030 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1779 Professional/industrial Association Standard

## How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1779R3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.