

Description

Length: 4-31/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1787A48G
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-579-7618
Schedule B:	7616.99.5090
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1787A48G Specifications

Overall Length:	4.494 Inches Nominal
Overall Width:	0.720 Inches Minimum And 0.780 Inches Maximum
Material Thickness:	0.160 Inches Minimum And 0.220 Inches Maximum
Distance Between Mounting Hole Centers:	3.919 Inches Minimum And 3.949 Inches Maximum
Cushion:	Not Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.219 Inches Minimum And 0.233 Inches Maximum
Distance Between Base And Inside Of Arch:	3.179 Inches Nominal
Inside Diameter/arch Length:	2.970 Inches Minimum And 3.030 Inches Maximum
Part Name Assigned By Controlling Agency:	Clamp, Tube Mounting
Special Features:	Has Aluminum Foil Wrap 0.007 Thick (per Qq-a-250/1 Temper O Tensile 12,000 Psi) Applied All Around Perimeter Of Clamp Base For Grounding
Material:	Plastic, Mil-m-20693, Comp A, Type 1
Material:	Plastic Polyhexamethylene Amide
Style Designator:	Saddle Arch

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1787A48G> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.