

**Description**

Length: 4-31/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1787A48G
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-579-7618
Schedule B:	7616.99.5090
ECCN:	9A991
National Motor Freight:	157170, Plastic / Rubr Straps / Rope / Cord / Strip

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1787A48G Specifications

<b>Overall Length:</b>	4.494 Inches Nominal
<b>Overall Width:</b>	0.720 Inches Minimum And 0.780 Inches Maximum
<b>Material Thickness:</b>	0.160 Inches Minimum And 0.220 Inches Maximum
<b>Distance Between Mounting Hole Centers:</b>	3.919 Inches Minimum And 3.949 Inches Maximum
<b>Cushion:</b>	Not Included
<b>Mounting Pad:</b>	Not Included
<b>Mounting Hole Size:</b>	0.219 Inches Minimum And 0.233 Inches Maximum
<b>Distance Between Base And Inside Of Arch:</b>	3.179 Inches Nominal
<b>Inside Diameter/arch Length:</b>	2.970 Inches Minimum And 3.030 Inches Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Clamp, Tube Mounting
<b>Special Features:</b>	Has Aluminum Foil Wrap 0.007 Thick (per Qq-a-250/1 Temper O Tensile 12,000 Psi) Applied All Around Perimeter Of Clamp Base For Grounding
<b>Material:</b>	Plastic, Mil-m-20693, Comp A, Type 1
<b>Material:</b>	Plastic Polyhexamethylene Amide
<b>Style Designator:</b>	Saddle Arch

## How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/NAS1787A48G> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.