

## **P/N NAS1789-06**

### **Description**

Thread Size: 1/8", Nut Length: 1/2", Nut Height: 1/4", NAS1789 series nut

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS178906

Minimum Qty (MOQ):

NSN: 5310-01-058-5388


Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







# **P/N NAS1789-06 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Distance From Centerline To Flat:	0.175 Inches Nominal
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.525 Inches Maximum
Nut Height:	0.203 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.490 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.250 Inches Nominal
Center To Center Distance Between Mounting Holes Along Width:	0.217 Inches Minimum And 0.221 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Special Features:	160000 Psi Min Tensile Strength
Material:	Steel Comp 1030 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1789 Professional/industrial Association Standard

## **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1789-06">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1789-06</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.