

Description

Thread Size: 1/4", Nut Length: 1/2", Nut Height: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS17893K
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-306-4861
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE
AVAILABLE

P/N NAS1789-3K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Distance From Centerline To Flat:	0.175 Inches Nominal
Lubrication:	Dry Film Lubricant
Overall Height:	0.250 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.525 Inches Nominal
Nut Height:	0.250 Inches Nominal
Plate Thickness:	0.032 Inches Nominal
Plate Width:	0.490 Inches Nominal
Nut Mounting Provision:	Dimpled Holes
Mounting Hole Arrangement Style:	2 Holes
Center To Center Distance Between Mounting Holes Along Width:	0.217 Inches Minimum And 0.221 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Special Features:	Sulfur And Phosphorus Content Shall Not Exceed 30by Weight
Material:	Steel Comp 1030 Overall
Material Document And Classification:	Sae 103 0 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1789 Professional/industrial Association Standard

How to Order

Order this plate locknut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1789-3K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.