

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS179033
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-045-2112
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1790-3-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Nominal
Fastener Length:	0.5255 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.381 Inches Nominal
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	36.0 Rockwell C Minimum And 42.0 Rockwell C Maximum
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-5626 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-8503 Mil Spec 5th Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1790-3-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.