

Description

Fastener Length: 1-9/32", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS17903R19 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-01-572-3435 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |



* See page 2 for technical characteristics

P/N NAS1790-3R19 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.338 Inches Nominal |
| Fastener Length: | 1.260 Inches Minimum And 1.290 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.339 Inches Minimum And 0.381 Inches Maximum |
| Internal Drive Style: | Torque Set |
| End Item Identification: | Nimrod 2000 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740 |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1790-3R19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.